

Cold 445CC Can Coolers and Freezers



Place your brand in high traffic areas



GreenSensePlus Features: Saving Energy and Reducing Lifetime Costs


Cyclopentane Insulation

High insulation.
Zero ODP (Ozone Depletion)
Negligible GWP (Global Warming Potential)



Low E Glass Lid

Improves insulation U value and reduces condensation




High Efficiency Compressor

Better CoP gives reduced energy consumption. Leading brand



R600a Refrigerant

More efficient. Zero ODP (Ozone Depletion) Negligible GWP (Global Warming Potential)




R a i s i n g s t a n d a r d s | R e d u c i n g c o s t s

Cold 445CC Can Cooler ~ 360 degree graphics



Standard Features:

- Strong castors for ease of movement, 2 locking
- Adjustable temperature control
- Baskets (2) included for ease of stock rotation



- Toughened glass flip/flop lid with Low E coating for improved insulation
- 360 degree branding available with removable wrap option
- Condensate water is automatically evaporated (chiller version only)
- Cooling system is within the cabinet walls

- Power cable is fixed in place (not detachable)

Optional Features:

- Solid hinged top on Cold 445S, 445 & 445T.
- Internal air circulating fan on selected models



Model	Coolers:				Freezers:			
	Cold 445 CCS	Cold 445CC	Cold 445CCT	Cold 565CC	Cold 445CCS-F	Cold 445CC-F	Cold 445CCT-F	Cold 565CC-F
	"Short"	"Standard"	"Tall"	"Wide"	"Short"	"Standard"	"Tall"	"Wide"
External Dimensions:								
Height with glass lid	735mm	960mm	1060mm	836mm	735mm	960mm	1060mm	836mm
Height with solid lid	815mm	1040mm	1140mm	N/A	815mm	1040mm	1140mm	N/A
Diameter	445mm	445mm	445mm	565mm	445mm	445mm	445mm	565mm
Internal Dimensions:								
Depth	392	617	717	493	392	617	717	493
Diameter	360	360	360	470	360	360	360	470
Temperature	2 - 12C	2 - 12C	2 - 12C	2 - 12C	≤ - 18C	≤ - 18C	≤ - 18C	≤ - 18C
Climate Class	3	3	3	3	3	3	3	3
Noise level Db	40	40	40	40	40	40	40	40
Voltage	220-240V	220-240V	220-240V	220-240V	220-240V	220-240V	220-240V	220-240V
Watts	100	100	127	120	100	100	127	120
Hertz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz
Amps (running)	0.7	0.7	1	1	0.7	0.7	1	1
Capacity Litres	40	65	77	85	40	65	77	85
Capacity 330ml cans	52	76	88	103	-	-	-	-
Capacity 500ml PET	24	40	48	57	-	-	-	-
Refrigerant	R600a	R600a	R600a	R600a	R600a	R600a	R600a	R600a
Container Loadings with glass lid:								
20 foot	155	120	120	80	155	120	120	80
40 foot	335	260	260	160	335	260	260	160
40 foot high cube	390	317	317	240	390	317	317	240
Container Loadings with solid lid:								
20 foot	150	120	102	N/A	150	120	102	N/A
40 foot	327	250	250	N/A	327	250	250	N/A
40 foot high cube	375	315	250	N/A	375	315	250	N/A



In the interests of continuous product development specifications may be changed without notice.

Staycold Export Ltd

9 Hunters Walk, Canal Street, Chester, CH1 4EB, United Kingdom

tel 01244 321320 | international tel +44 1244 321320

web: www.staycold.co.uk | email: sales@staycold.co.uk