

Instructions for Cleaning the Condenser on your STAYCOLD Cabinet

In common with most commercial refrigeration, the condenser on your Staycold cabinet must be kept clean and free of dust at all times. The function of the condenser is to dissipate the heat that has been taken from inside the cabinet. It is recommended that you check the condenser every three months to ensure peak efficiency. If the condenser is not kept clean, the compressor will be forced to run longer meaning higher energy bills, shortened compressor life and less effective cooling. In the worst case it will cause premature compressor failure. The warranty on the cooler is invalidated by a dirty condenser. To clean the condenser, please take careful note of the following instructions and procedure:

Step 1



Unplug the cooler from the mains electricity supply.



Step 2

Remove the bottom grille underneath the glass doors. Simply lift the grille slightly and pull away from the retaining lugs. No tools are necessary.

Caution: Some pipework and components may be very hot to the touch and there is a risk of burning the skin.



Step 3

Locate the condenser. It has an appearance similar to a car radiator and is to be found next to and attached to the fan.



Step 4

One side of the condenser may have a build up of dust and debris. It should never look as bad as this example! If it looks as bad as this, the cooler will be running at less than 50% efficiency and will be heading for the refrigeration equivalent of a heart attack.



Step 5

Take a soft brush and clean the fins. Caution: The condenser is a very delicate component and it is easily damaged. Be careful not to bend the fins. Never poke anything through them. Never use water. Only use a soft brush. Do not use a wire brush or a stiff brush.



Step 6

Ideally use a vacuum to clear away the debris. If no vacuum available, then please carefully brush away and remove the debris. At the same time, check the rest of the compressor compartment for foreign objects, such as wrappers, bottle tops etc and remove them carefully.



Step 7

Ensure all tools have been removed and then refit the grille.



Step 8

Plug back in to the mains electricity supply. Log the date of cleaning and make a diary note to clean it again in 3 months or sooner if a very dusty environment.



Always use Genuine Staycold parts. See website for details.
www.staycold.co.uk