Cold 430 CTS
Counter Top Cooler

rhino
www.rhinoequipment.eu

A versatile beverage cooler ideal for promotional use

GreenSense Features: Saving Energy and Reducing Lifetime Costs

LED lighting
Longer lifetime and greatly reduced heat in the cabinet so less work for refrigeration unit

Cyclopentane foam
High insulation. Zero ODP (Ozone Depletion) Negligible GWP (Global Warming Potential)

R600a Refrigerant
More efficient. Zero ODP (Ozone Depletion) Negligible GWP (Global Warming Potential)

Raising standards | Reducing costs

Cold 430 CTS Counter Top Cooler

Capacity Data:

Glass bottle 330ml (Corona)	50	Can 250ml (Red Bull)	96	PET Bottle 500ml (Vimto)	33
Glass bottle 568ml (Bulmers)	28			PET Bottle 500ml (Evian)	40
				PET Bottle 380ml (Lucozade)	50

Cabinet Features

- Lock
- LED Interior light with switch
- Shelves - 2 full size plus floor shelf
- Reversible door hinge

- Adjustable temperature control
- Skin condenser: This means the heat is disipated via the outside walls and so they must not be covered by anything thicker than a decal.

External Dimensions (mm)	
Height	645
Width	430
Depth without handle	480
Depth with handle	520
Ventilation space	20mm must be allowed for around the cabinet

Internal Dimensions (mm)	
Height	540
Width	350
Depth	230 at base or 375 at middle

Container loading	
20 foot	174
40 foot	374
40 foot high cube	460

Specifications	
Climate Class	3 (25C / 60% Relative Humidity)
Gross Weight	24 kg
Nett Weight	22 kg
Noise Level in Db	39 Db
Voltage	220- 240 Volts
Hertz	50 Hz
Rated Power	85 Watts
Running Current	0.55 Amps
Energy Rating	B
Refrigerant	R600a

Choose **GreenSense** to improve energy efficiency and reduce lifetime costs. To find out why being environmentally conscious is also good for the cost conscious, please visit **www.greensenseplus.com**

Staycold Export Ltd

9 Hunters Walk, Canal Street, Chester, CH1 4EB, United Kingdom

tel **01244 321320**   fax **01244 322345**
international tel **+44 1244 321320**
email **sales@staycold.co.uk**

In the interests of continuous product development specifications may be changed without notice.